




**Step 6:** Remove the add-a-quarter and fold template. Place the fabric piece for Sec. 2, **right-side-up** next to the folded back paper as shown.

**Step 7:** Lift the foundation paper and slide the fabric under Sec. 2. Notice on the graphic where Sec. 2 is located on the **backside** of the paper. Line up the second fabric with the trimmed quarter-inch seam allowance.



**Step 8** Lift the two (2) pieces to your machine with the paper. Open the paper and sew on Line 1. Start at the top of the fabric and sew just past the end of Line 1. Always extend the sewing lines beyond the dotted lines.

**Note:** Remember if you sew through the seam allowance just past the dotted line on the foundation, when you fold back to trim the seam allowance it will automatically trim the loose threads from the backside of the paper.

**Step 9:** Loosen the glue under Sec. 1 at this time and press the fabrics open on the backside of the paper.




Continue sewing each piece onto the foundation paper. Remember to press, fold, and trim as each piece is added to the paper. When the foundation piecing is completed for the right units, trim the excess fabric off with your rotary cutter. Set the pieces back into Bag #4 and return to complete the left units.



**Note:** Do not remove the foundation papers at this time.

**Unit C1-L:** Make eight (8) left units. The left unit is a mirror image of the right unit, but the paper piecing steps are the same. Complete the piecing using the previous 10 steps.




## Part Two, Unit C-2, Bag #5, Make (8) Right and (8) Left.



**Step 1:** Position the foundation paper for **Unit C2-L**, right-side-up on your table.

**Note:** Turn the paper over and trace the dotted lines on the backside of the first piece.

**Step 2:** Place a small amount of glue on the backside of the paper under Sec. 1.



**Step 3:** Lift the foundation paper and position Sec. 1 onto fabric #1 with the wrong-side of the paper glued to the wrong-side of the fabric. Make sure the underneath side of Sec. 1 is covered. The fabric must extend beyond the dotted lines located next to Sec. 1.

