- Sew the sashing strips to the diamond and . press both seams towards the sashing.
- The long sashing strips T-Template AA-3B and AA-4B are sewn . onto the top and bottom edge (Rows 1 and 4) of each diamond.
- Press both seams toward the sashing.

Round C: Steps 1 to 5 for Round C are shown in the Sashing Assembly Graphic, Illustration 4. The Steps are identical to that for Round A. The Templates used, however, are T-Template AA-1C and AA-2C on the top and bottom edges (Rows 1 and 4). The Templates for the sides are T-Template AA-3C and AA-4C. Press all seams towards the sashing strips.

GROUP B: BACKGROUND T-TEMPLATES

Ziploc Storage Bags: You will need (1) Bag to complete the organization for these instructions. Label and organize the cutting templates as follows:

Bag #B1, T-Templates B1L-B4L and B1R-B4R

Preparing the Foundation Papers:

Step 1: Cut out (1) of each T-Template B1L to B4L and B1R to B4R. [TP 382 & TP 383]. Place these into Bag #B1. *Refer back to General Information Booklet for Foundation papers and templates for additional instructions on how to prepare your foundation papers and templates.

NOTE - Formatting Changes: You may notice your pattern looks different on Pages 12, 13, and 14 than your neighbors. The text that was originally at the top of Page 12, 2nd column should have been with the graphic in the 2nd column of Page 14. This text has been moved. But, none of the pattern information has changed...only formatting!

