Step 10: Open the paper, sew on Line 2, and press.

Step 11: Continue adding the remaining fabric pieces to each section on the foundation papers.

Step 12: When the paper piecing is completed, set your stitch length on your machine to sew a basting stitch (see TRP section on page 5 under General Piecing Instructions). Sew the (TRP) lines, then trim the excess paper and fabric off around the perimeter of the printed Unit C1 paper; remember to trim the Smart Corners! Place these pieces back into Bag #B1.

> **NOTE - Paper:** The foundation paper is not removed until you are ready to assemble the Block Groups.

Step

10

Press

► Foundation Paper Piecing: Unit C2

Stacking and paper piecing for Unit C2 is the same as Unit C1, so the previous steps provided for Unit C1 are the same. Just remember the Unit C2 papers are mirror images of Unit C1 so the images in the graphics will appear to be upside down. When the paper piecing is completed, set your stitch length on your machine to sew a basting stitch (see TRP section on page 5 under General Piecing Instructions). Sew the (TRP) lines, then trim the excess paper and fabric off around the Unit C2 perimeter of the printed paper. Place the Unit C2 pieces back into Bag #C2. (Graphics were not provided for Unit C2.)

STACKING: UNITS C3 & C4, BAGS #C3, #C4

Stacking: Position Alt Temp-1 with Temp C3-6 as shown for Unit C3 facing right-side up, with the sew-sides aligned at the top. Stack the pieces with Alt Temp-1 on top.





Unit C4



shown for Unit C4 facing right-side up, with the sew-sides aligned at the top. Stack the pieces with Alt Temp-2 on top.

FOUNDATION PAPER PIECING: UNITS C3 & C4



NOTE - Tracing Dashed Lines: Optional

Step 1: Position the first piece of fabric for Unit C3 (Alt Temp-1) wrong-side-up on your table. Lift the foundation paper, and slide the fabric

Step 1

under Sections 1–5. Glue is used to adhere the fabric



to the backside of the paper. Repeat Step 1 for each foundation paper before moving on to Step 2. old Back

Paper Step 2: Position the fold template over the top of Sections 1-5, lining the edge up with Line 5 for Unit C3 (Line 6 for Unit C4). Fold back the paper.

Step 3: Place the Add-A-Quarter ruler next to the folded-back paper, and trim the fabric with the rotary cutter.



Step 4: Place the second fabric piece for Unit C3 (Sec. 6) right-side up next to the foldedback paper, then lift the paper, and

slide the fabric under Sec. 6.

Step 5: Open the paper and sew on *Line 5*, then press the fabric on the backside of each paper.



Step

Step 6: When the paper piecing is completed, sew the TRP lines, then trim the excess paper and fabric off around



the perimeter of the printed paper. Trim the Smart Corners. Repeat the same piecing steps to complete the alternative piecing for Unit C4. Place both units into their assigned Bag #s.

BLOCK ASSEMBLY



Assembly: At left are graphics showing the exploded view of the Block Assembly. Set your sewing machine to sew a 1/4" seam. Follow the remaining assembly illustrations and press seams Unit C1 in the direction the arrows are pointing.

Step 1: Remove papers from each unit just prior to sewing units together. Match the smart corners at the beginning and end of each seam. Fabric glue is used to secure the smart corners and raw edges of your

Unit

seam allowance as you sew the block groups together.

Step 2: Working left to right and using curved seams, join the following pieces:

- Join Unit C2 to C4. Press toward Unit C2.
 - Join Unit C1 to C3. Press toward Unit C1

21



To avoid Y-seams in

the assembly process, the (8) Sail Units are NOT joined at this time. The pieces are set aside until

all the paper piecing is completed for the remaining groups in your pattern.